



DES-1008F

8-Port 10/100Mbps Switch With 100BASE-FX Fiber Port

The DES-1008F is an 8-port 10/100Mbps compact desktop switch that is an ideal choice for the small workgroup. This switch allows users to simply plug any port to either a 10Mbps Ethernet or 100Mbps Fast Ethernet network for compatibility, convenience and faster connection. This switch also provides a 100BASE-FX for a secure connection of a server on a fiber network cable.

Designed for SOHO

The DES-1008F comes in a small compact size designed for use by SOHO with easy installation and high performance. The switch eliminates unnecessary traffic and relieves data congestion by delivering dedicated bandwidth for each of the 8 ports.

7 10/100BASE-TX Ports for Plug and Play Connections

Each of the 7 10/100BASE-TX ports supports automatic MDI/MDIX detection, providing true plug and play capability without the need for confusing crossover cables or crossover ports. With the media auto-sensing feature, you can plug in the network cable to the switch directly without the need to worry if the end node is a NIC (Network Interface Card) or switch/hub. The switch also supports flow control and auto-negotiation of half or full duplex transfer modes for each port.

100BASE-FX Fiber Port for Server Connection

The switch provides a fiber port capable of transferring data at long cable distance. This port can be used to connect to a server over the reliable fiber cable, or to attach the switch to the network fiber backbone.

Fast & Reliable Data Transfer

With 802.3x flow control support and fast store-and-forward switching scheme, the DES-1008F gives you secure data transfer with low data latency that prevents error packages from transmitting among segments.

Key Features

- Cost-effective packet switching network for SOHO
- 7 10/100BASE-TX ports for workstation connection
- 1 100BASE-FX port for fiber connection
- Auto MDI/MDIX for all twisted-pair ports
- Secure store-and-forward switching scheme
- Full/half-duplex support
- 802.3x flow control to minimize packet loss
- Plug-and-play installation
- Compact desktop size

DES-1008F

Technical Specifications

10/100Mbps Unmanaged Switch

General

Standards

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX/100BASE-FX Fast Ethernet
- ANSI/IEEE 802.3 NWay auto-negotiation
- IEEE 802.3x Flow Control

Protocol

CSMA/CD

Data Transfer Rates

- **Ethernet:**
 - 10Mbps (half duplex)
 - 20Mbps (full duplex)
- **Fast Ethernet:**
 - 100Mbps (half duplex)
 - 200Mbps (full duplex)

Topology

Star

Network Cables

- **10BASE-T:**
 - 2-pair UTP Cat. 3, 4, 5 (100 m)
 - EIA/TIA-586 100-ohm STP (100 m)
- **100BASE-TX:**
 - UTP Cat. 5 (100m max.)
 - EIA/TIA-568 100-ohm STP (100m max.)
- **100BASE-FX:**
 - 62.5/125um multimode fiber (2km max.)

Full/half Duplex

Full/half duplex for 10/100Mbps speeds

Media Interface Exchange

Auto MDI/MDIX for all twisted-pair ports

LED Indicators

- Per port: 10/100Mbps speed, Full Duplex/Collision
- Per device: Power

Performance

Transmission Method

Store-and-forward

MAC Address Learning

Automatic update

Packet Filtering/Forwarding Rates (half duplex)

- Ethernet: 14,880 pps per port
- Fast Ethernet: 148,810 pps per port

Physical & Environmental

DC Input

7.5V/1A

Power Supply

Through external power adapter

Dimensions

192 (W) x 117 (D) x 32 (H) mm (device only)

Weight

314 grams (device only)

Operating Temperature

0° to 40 °C

Storage Temperature

-20° to 75 °C

Operating Humidity

10% to 90% non-condensing

Storage Humidity

5% to 90% non-condensing

Emission (EMI)

- FCC Class B
- CE Class B
- C-Tick



Ordering Information

Fast Ethernet Switch With Fiber Port
DES-1008F 7 10/100BASE-TX ports, 1 100BASE-FX port

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc.
All other trademarks belong to their proprietors.

U.S.A	TEL: 1-949-788-0805	FAX: 1-949-753-7033
Canada	TEL: 1-905-8295033	FAX: 1-905-8295095
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Benelux	TEL: 31-10-282-1445	FAX: 31-10-282-1331
Italy	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Norway	TEL: 47-22-309075	FAX: 47-22-309085
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-3-8899-1800	FAX: 61-3-8899-1868
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
China	TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914
Middle East	TEL: 9714-8834234	FAX: 9714-8834394
Turkey	TEL: 90-212-335-2553	FAX: 90-212-335-2500
Chile	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
South Africa	TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE
Rev. 02 (Oct. 2003)