

Product Highlights

Output To 3 Displays Simultaneously

Multi-Stream Transfer allows connection to 3 external displays at the same time, enabling greater productivity

Full-Resolution Video

HDMI resolution up to 4K @ 30 Hz Ultra HD, DisplayPort resolution up to 4K @ 60 Hz Ultra HD, and VGA resolution up to Full HD 1080p @ 60 Hz for stunning videos and images with no lag

No Installation Required

Simply connect to an available USB Type-C or Thunderbolt 3 port and enjoy HDMI, DisplayPort, or VGA video in seconds; no further installation necessary



DUB-V310

3-in-1 USB-C to HDMI/VGA/DisplayPort Adapter

Features

Multi-Stream Transfer

- Windows: 3 outputs simultaneously, with HDMI 4K @ 30 Hz, DisplayPort 4K @ 30 Hz and VGA 1080p @ 60 Hz
- Macintosh: 3 outputs simultaneously, with HDMI 1080p @ 60 Hz, DisplayPort 1080p @ 60 Hz and VGA 1080p @ 60 Hz

HDMI Compatibility

- Ultra HD video resolution up to 4K @ 30 Hz
- Supports HDMI 1.4 and DisplayPort Alternative Mode over USB-C
- HDCP 2.2 Compatible

VGA Compatibility

- Full HD video resolution up to 1080p @ 60 Hz

DisplayPort Compatibility

- Ultra HD video resolution up to 4K @ 60 Hz¹
- DisplayPort 1.2
- DisplayPort Dual Mode (DP++)


USB Type-C 3.0 with Simple Installation

- Simply plug and play, no software required
- Small and compact design makes it easy to take with you wherever you go

The DUB-V310 3-in-1 USB-C to HDMI/VGA/DisplayPort Adapter allows you to instantly add additional displays to your ultraportable laptop. Just plug the DUB-V310 into an available USB Type-C or Thunderbolt 3 port and you are ready to expand your desktop workspace or display on an additional/larger screens.

The Multi-Stream Transfer feature allows you to distribute the signal across multiple monitors simultaneously. This allows for the display of content on three outputs at the same time on a Microsoft Windows or Macintosh OS system.

Hardware Overview



DUB-V310 3-in-1 USB-C to HDMI/VGA/DisplayPort Adapter

Technical Specifications

Connectivity

| | | |
|-------------------|--|--|
| Device Interfaces | <ul style="list-style-type: none">• HDMI Port (3840 x 2160 or 4096 x 2160 pixels @ 30 Hz)• VGA Port (1920 x 1080 or 1280 x 720 pixels @ 60 Hz) | <ul style="list-style-type: none">• DisplayPort (3840 x 2160 or 4096 x 2160 pixels @ 60 Hz)¹• USB Type-C Connector (Thunderbolt 3 compliant) |
| Standards | <ul style="list-style-type: none">• USB Specification Version 3.1 Gen 1• USB Specification Version 2.0• USB Specification Version 1.1• HDMI 1.4 | <ul style="list-style-type: none">• DisplayPort 1.2• DisplayPort Dual Mode (DP++)• HDCP 2.2• DisplayPort Alternative Mode |

General

| | | |
|-----------------------------|--|---|
| Minimum System Requirements | <ul style="list-style-type: none">• Computer running Microsoft Windows, Mac OS, or Chrome OS | <ul style="list-style-type: none">• Available USB Type-C Port with DisplayPort Alternate Mode Supported |
|-----------------------------|--|---|

Physical

| | | |
|----------------|--|---|
| Dimensions | <ul style="list-style-type: none">• 62.5 x 40.5 x 15.0 mm | <ul style="list-style-type: none">• Cable length: 110 mm |
| Weight | <ul style="list-style-type: none">• 44 g | |
| Power | <ul style="list-style-type: none">• Input: Bus-powered | <ul style="list-style-type: none">• Consumption: 40 mA, 5 V DC |
| Temperature | <ul style="list-style-type: none">• Operating: 0 to 45 °C (32 to 113 °F) | <ul style="list-style-type: none">• Storage: -10 to 70 °C (14 to 158 °F) |
| Humidity | <ul style="list-style-type: none">• Operating: 10% to 85% RH, non-condensing | <ul style="list-style-type: none">• Storage: 5% to 90% RH, non-condensing |
| Certifications | <ul style="list-style-type: none">• CE• FCC | <ul style="list-style-type: none">• IC• RCM |

¹ Regarding the Windows System: Supports different displays on 3 outputs simultaneously, with HDMI 4K @ 30 Hz, DisplayPort 4K @ 30 Hz and VGA 1080p @ 60 Hz. Regarding the Macintosh System: Supports mirroring displays on 3 outputs simultaneously, with HDMI 1080p @ 60 Hz, DisplayPort 1080p @ 60 Hz and VGA 1080p @ 60Hz



For more information: www.dlink.com

D-Link European Headquarters. D-Link (Europe) Ltd., First Floor, Artemis Building, Odyssey Business Park, West End Road, South Ruislip HA4 6QE, United Kingdom. Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners. ©2019 D-Link Corporation. All rights reserved. E&OE.

Updated September 2019

D-Link[®]