



DI-784

AirPremier AG

Up to
15X
Faster

Dualband



802.11a/g Tri-Mode Dualband Wireless Router

With Built-in 4-Port Switch

The D-Link AirPremierAG DI-784 wireless router is a four-port, tri-mode, dualband device that provides the most expanded user bandwidth available in a router. Hundreds of wireless clients can connect to this router using any one of its non-overlapping channels to transfer data at speeds up to 15 times faster than 802.11b previous wireless devices.

Dualband Operation

The DI-784 operates seamlessly and simultaneously in both the 2.4GHz and 5GHz frequency spectrums supporting the 802.11b and the newer, faster 802.11a and 802.11g wireless standards. For offices, schools or public hotspots that already use 802.11b devices, the DI-784 is a great way to expand an existing network that enables more users to communicate with one another, access data and the Internet. Now, you can have a router that compliments your existing network and protects the investment you made when you provide the convenience of wireless networking.

Fast Network Data Transfer

The DI-784 offers network data transfer rates of up to 108Mbps Turbo Mode in 11g mode and 54Mbps in 11a mode. So, now large data packets can travel from the router to a remote desktop or roaming laptop PC at up to 15 times the throughput of previous 802.11b wireless devices, enabling everyone to work faster and more efficiently or watch a streaming video smoothly.

Network Segmentation

Network administrators can partition the usage of the DI-784 by segmenting users on the wireless network by frequency band. Users who require special networking privilege access to sensitive company data, video conferencing, or connectivity to specific departments may use just the 802.11a channels, while other employees may just use the 802.11b and 802.11g channels. This type of user

segmentation optimizes the router's performance and delivers the best network experience to each set of users.

Enhanced Security

The DI-784 is ideal for those who require additional management, firewall, and other network security features such as the 802.1x standard for wireless user authentication and WPA* (Wi-Fi Protected Access) which dynamically encrypts data as it's being sent. And because the DI-784 allows the pass-through of multiple, concurrent IPSec and PPTP VPN sessions, IT managers can deploy the DI-784 to their company's telecommuters and other remote employees who need to access sensitive information from a server or database or to communicate to a colleague confidentially. Filters on the router can be set to restrict access based on the specific MAC addresses of wireless laptop or desktop cards on the network, or restrict the access of IP addresses, specific websites and/or web domain names. All of the router's settings are easily accessible in the operating system independent, Web-based software user interface that also features a step-by-step Setup Wizard to get the DI-784 up and running in just a matter of minutes.

Built-in 4-Port Switch

The DI-784 features an integrated 4-port switch allowing direct Ethernet connection to up to four computers for additional Internet or resource sharing at wire speeds.

Key Features

- 802.11a/g industry standard
- Dual 5GHz and 2.4GHz frequency bands
- Up to 108Mbps performance in 11g and 54Mbps in 11a, up to 15 times faster than 802.11b throughput
- Wireless LAN security with user-selectable 64/128/152-bit
- WEP data encryption and Wi-Fi Protected Access (WPA)
- Backward compatible with existing 802.11b wireless devices
- Multi-user wireless broadband access
- Advanced firewall security with Stateful Packet Inspection (SPI), security event log
- User level control, domain filtering, URL blocking
- Integrated 4-port Fast Ethernet switch
- Network Timing Protocol (NTP), UPnP support
- Easy-to-use web-based configuration/management
- Setup Wizard for quick installation

Wireless LAN**Device Ports & Interface**

- 10/100BASE-TX WAN port supporting PPPoE for DSL/cable modem connection
- 4 10/100BASE-TX Ethernet switch ports with auto MDI/MDIX
- WLAN supporting 802.11g, 802.11b, 802.11a standards

Wireless LAN Data Rates

(With Automatic Fallback)

- 54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps

WLAN & Ethernet Media Access Control

CSMA/CA with ACK

RF Frequency Range *

- 2.4GHz to 2.4835GHz
- 5.15GHz to 5.250GHz
- 5.725GHz to 5.850GHz

* Software configurable as allowable frequency will vary from country to country

Operation Channels (802.11b and 802.11g)

- 11 channels (North America)
- 13 channels (General Europe)

Operation Channels (802.11a)

- 4 Channels: 5.12 to 5.25 GHz for channel 36, 40, 44, 48
- 4 Channels: 5.25 to 5.35 GHz for channel 52, 56, 60, 64
- 11 Channels: 5.47 to 5.725 GHz for channel 100-140

Dynamic WLAN Channel SelectionAuto-selecting the least utilized channel of operation
DFS and TPC support**WLAN Modulation Technology**

Direct Sequence Spread Spectrum (DSSS)

WLAN Modulation Scheme

- Orthogonal Frequency Division Multiplexing (OFDM)
- Complementary Code Keying (CCK)
- BPSK/QPSK/16-QAM/64-QAM

Antennas

1 external dipole 2dBi Gain antenna supporting 2.4GHz and 5GHz frequency bands (non-detachable)

Operation Range

- Indoors: up to 100 meters *
- Outdoors: up to 300 meters *

* Environmental factors may adversely affect operation range.

Wireless Receiver Sensitivity (802.11a and 802.11g)

(typically @PER < 10% packet size 1024 @ 25°C +/- 5°C)

- 54Mbps (OFDM): -73dBm
- 48Mbps (OFDM): -76dBm
- 36Mbps (OFDM): -82dBm
- 24Mbps (OFDM): -85dBm
- 18Mbps (OFDM): -88dBm
- 12Mbps (OFDM): -89dBm
- 9Mbps (OFDM): -90dBm
- 6Mbps (OFDM): -91dBm

Wireless Receive Sensitivity (802.11b)

(typically @PER < 8% packet size 1024 @ 25°C +/- 5°C)

- 11Mbps (CCK): -91dBm
- 5.5Mbps (CCK): -92dBm
- 2Mbps (QPSK): -93dBm
- 1Mbps (BPSK): -94dBm

Wireless Transmit Power Output

15 +/- 2dBm (typical)

Wireless LAN Security

- 64/128/152-bit WEP user-selectable
- WPAEAP, WPA PSK

Router, Security & Management**Standards & Protocols**

- TCP/IP v4, UDP, ICMP
- Management: HTTP
- DHCP, NAT, DNS
- Routing: RIP v.1, RIP v.2
- Security: PAP, CHAP
- VPN pass through: L2TP, PPTP, IPSec

Network

- Automatic configuration to use DNS, NAT and Web services
- DHCP Server/Client, Static Router, PPPoE, PPTP support
- VPN pass-through support for L2TP, PPTP, IPSec
- UPnP support

NAT/PAT

- Virtual DMZ host (1 entry)
- Virtual Server Mapping (10 entries)
- Shares single IP addresses/ISP account from the cable or DSL on local network

PPPoE Support

- Compatible with most cable and DSL ISP
- PPP connection on demand to save ISP connection fee

Router & Firewall Security

- Password Protect
- MAC Filtering
- SSID broadcast disable
- Access-list control and rules
- Stateful Packet Inspection (SPI)
- Domain Filtering
- URL Filtering
- Packet Filtering
- Ping of Death prevention
- IP spoofing
- Intrusion Detection
- Security event log

Configuration & Management

- Web-based configuration utility
- Status log
- Network Time Protocol (NTP)

Diagnostic LEDs

- Power
- WAN
- LAN (10/100Mbps)
- WLAN (wireless connection): 802.11a, 802.11g

Physical & Environmental**Power Input**

- DC 5V, 3.0A
- Through external power adapter

Dimensions

192 mm (L) x 118 mm (W) x 32mm (H) (device only)

Weight

850 grams approximately (device only)

Operating Temperature

0° to 55°C

Storage Temperature

-20° to 65°C

Humidity

5% to 95% (non-condensing)

Emission (EMI)

- FCC Part 15 Class B, Sec. 15.247, 15.109
- ETS 300 328, ETS 301 489-1&17, and CE Mark
- EN 60950, EN 55022 Class B, EN 50082-1 1998



Ordering Information

DI-784 802.11a/g Wireless Router With Built-in 4-Port Switch

Please specify your order as follows:

BDI-784	For USA (USA packaging)
CDI-784	For Canada
TDI-784	For Taiwan
NDI-784	For China
DI-784/NAU	For Australia
DI-784/ESG	For Singapore
DI-784/ALA	For Latin America (with US standard power adapter)
DI-784/ELA	For Latin America (with EU standard power adapter)
DI-784/EFR	For France and Slovak
DI-784/EEU	For Denmark, Germany, Iceland, Finland, Netherlands, Norway, Sweden, Poland, Slovenia, Luxembourg, South Africa
DI-784/BEU	For UK, Ireland



Specifications subject to change without prior notice.
D-Link is a registered trademarks and AirPremier AG is a trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A	TEL: 1-714-885-6000	FAX: 1-866-743-4905
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500
Italy	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Norway	TEL: 47-23-897189	FAX: 47-22-309085
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
China	TEL: 86-10-5863-5800	FAX: 86-10-5863-5799
India	TEL: 91-022-2652-6696	FAX: 91-022-2652-8914
Middle East (Dubai)	TEL: 9714-3916480	FAX: 9714-3908881
Turkey	TEL: 90-212-335-2553	FAX: 90-212-335-2500
Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Latin America	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-55039320	FAX: 55-11-55039322
South Africa	TEL: 27-1266-52165	FAX: 27-1266-52186
Russia	TEL: 7-095-744-0099	FAX: 7-095-744-0099#350
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299