

## **Product Highlights**

### **Full Resolution Video**

HDMI video up to 4K @ 30 Hz Ultra HD resolution for stunning videos and images with no lag

#### **Easy Expansion**

Easily add  $4 \times USB 3.0$  ports to any laptop or computer with a spare USB-C port. Simply plug in, no need to install additional software

### Ultra-Fast USB 3.0

SuperSpeed USB 3.0 technology allows you to transfer files up to 10 times faster than with USB 2.0



## **DUB-2333**

## 5-in-1 USB-C Hub with HDMI/Power Delivery

### **Features**

**High Fidelity Video Compatibility** 

• Ultra HD video resolution up to 4K @ 30 Hz1

### **Versatile and Convenient**

- Three USB 3.0 SuperSpeed 5 Gbps ports
- One USB 3.0 Type-C port with power delivery of up to 60 W (20 V @ 3 A) $^{2}$
- Simply plug-and-play, no software required
- Compact design
- Compatible with Windows and macOS computers, Chromebooks and iPad Pro

The DUB-2333 5-in-1 USB-C Hub with HDMI/Power Delivery allows you to instantly add a second display and three additional USB 3.0 ports to your Windows and macOS computers, Chromebooks and iPad Pro. Just plug the DUB-2333 into an available USB-C port and you're ready to send content to your TV or monitor in full resolution, as well as connect up to three more USB devices.

### **Hardware Overview**



# 5-in-1 USB-C Hub with HDMI/Power Delivery

Technical Specifications		
Connectivity		
Interfaces	One USB Type-C connector Three USB 3.0 Type-A ports	One USB Type-C/PD 3.0 port One HDMI port
LEDs	Power (per device)     Solid green - power is on	
General		
Standards	• USB 3.0 • USB 2.0 • USB 1.1	
Data rate	• Up to 5 Gbps	
Resolution	• 4K @ 30 Hz	
System requirements	Windows 7/8/8.1/10, macOS (OS X 10.8 and above)     Chromebook, iPad Pro	USB Type-C port supporting DP Alt (DisplayPort Alternate Mode) for HDMI output
Physical		
Dimensions (W x H x D)	• 118 x 35 x 13.5 mm	
Weight	• 70 g	
Power	From computer (USB bus powered)	
Supplied charging voltage/current	• 20 V / 3 A (PD 3.0)	
Temperature	• Operating: 0 to 45 °C	• Storage: -10 to 70 °C
Humidity	Operating: up to 85% non-condensing	Storage: up to 85% non-condensing
Certifications	• CE	

<sup>&</sup>lt;sup>1</sup> Please make sure that the USB Type-C port of your computer supports DP Alt (DisplayPort Alternate Mode). <sup>2</sup> Please make sure that the USB Type-C port of your laptop supports PD 3.0.





