



DP-300U

Print Server with 2 parallel ports, 1 USB port

## 3-Port Print Server

The DP-300U multi-port print server is designed to share a cluster of printers located at a central site such as a data center or a computer room. It is equipped with 2 parallel printer ports and 1 USB port, allowing 2 parallel printers and 1 USB printer to be shared over the network. Supporting multiple network operating systems, this device brings a high level of flexibility and performance to your office printing needs.

### Multiple Ports Save Cost

With 3 printer ports available from a single device, you don't need to purchase and install a separate print server for each printer. This multi-port print server is only slightly more expensive than a single-port print server. Where your printers are closely placed together, it makes sense to buy a single print server instead of three. Each of your printers is connected to a printer port on the server through a printer cable.

### Simultaneous Printing on All Printers

Equipped with a powerful CPU, large memory and high-speed printer ports, this print server makes printing of your network files fast. All printers attached to this device can print their print jobs at the same time, giving your multi-port print server a similar performance as that of 3 separate single-port print servers.

### Multiple Network OS Support

The DP-300U supports as many network OS as these: Windows 95, 98, ME, NT 4.0, XP, Apple MacOS with AppleTalk, Linux, Solaris, SCO Unix, IBM AIX and NetWare 5.x native NDS. Better yet, you can configure different OS on different printers and have them print at the same time. This gives you all the flexibility when you select the DP-300U.

### Bi-directional Printer Communication

HP PJJ protocol is supported for bi-directional network printer communication, providing you with critical information about the network printer.

---

### Key Features

- 2 parallel printer ports, 1 USB 1.1 port supporting USB printer
- Multiple printer ports ideal to share out cluster of printers
- Auto-sensing 10/100Mbps Fast Ethernet port easily connects to network
- Windows-based administrative program for easy setup/management of print jobs
- Bi-directional communication to collect and report information/status of attached printers
- Large flash memory with easy software upgrade
- SNMP and MIB-II (RFC 1213) support for platform-independent management
- Easy web-based configuration from any browser

# DP-300U

## Technical Specifications

## Print Server

### Printer Ports

- 2 DB-25 IEEE 1284 bi-directional parallel ports
- 1 USB 1.1 port

### LAN Port

RJ-45 10/100Mbps auto-sensing 10BASE-T/100BASE-TX port

### Parallel Port Bi-directional Communication

Hewlett-Packard PJI (Printer Job Language) support

### Network Protocols

- Transport Protocols: TCP/IP, NetBEUI, AppleTalk/EtherTalk
- TCP/IP Protocols: BOOTP, SNMP, Telnet, TFTP, FTP, LPD, RARP, DHCP

### Management and Diagnostics

Standard: SNMP  
MIBs: MIB-II (RFC 1213)

### Configuration Reset

Reset button

### Flash memory

512K Bytes

### Diagnostic LED Indicators

- Power
- Link/Act
- USB
- LPT1
- LPT2

### OS Support

- Windows 95, 98, ME, NT 4.0, XP
- Apple MacOS with AppleTalk
- Linux
- Solaris
- SCO Unix
- IBM AIX
- NetWare 5.x native NDS

## Environmental & Physical

### Input Power

- 5V DC/ 2.5A
- Through external power adapter

### Dimensions

193 mm (W) x 117 mm (D) x 34mm (H)

### Weight

Approx. 300 grams

### Operating Temperature

0°C to 50°C

### Storage Temperature

-25 to 55°C

### Humidity

5% to 95% non-condensing

### Emissions

- FCC Class B
- CE Class B
- C-Tick
- UL
- LVD (EN60950)

### Box Includes

- DP-300U device
- CD-ROM with Manual and Print Server Administration program
- Quick Installation Guide
- External power adapter



LISTED  
ITE  
E141136  
66F9



ACN 052 202 838

## Ordering Information

### 3-Port Print Server

**DP-300U** 2 parallel printer ports, 1 USB 1.1 port

*Please specify your order as follows:*

<b>DP-300U/A</b>	With US standard power adapter
<b>DP-300U/B</b>	With UK standard power adapter
<b>DP-300U/E</b>	With EU standard power adapter
<b>DP-300U/CN</b>	With China standard power adapter
<b>DP-300U/N</b>	With Australia standard power adapter

# D-Link®

Specifications subject to change without prior notice.  
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

<b>U.S.A</b>	TEL: 1-949-788-0805	FAX: 1-949-753-7033
<b>Canada</b>	TEL: 1-905-8295033	FAX: 1-905-8295095
<b>Europe</b>	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
<b>Germany</b>	TEL: 49-6196-77990	FAX: 49-6196-7799300
<b>France</b>	TEL: 33-1-30238688	FAX: 33-1-30238689
<b>Benelux</b>	TEL: 31-40-2668713	FAX: 31-40-2668666
<b>Italy</b>	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
<b>Iberia</b>	TEL: 34-93-4090770	FAX: 34-93-4910795
<b>Sweden</b>	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
<b>Norway</b>	TEL: 47-22-991890	FAX: 47-22-205700
<b>Denmark</b>	TEL: 45-43-969040	FAX: 45-43-424347
<b>Finland</b>	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
<b>Singapore</b>	TEL: 65-6774-6233	FAX: 65-6774-6322
<b>Australia</b>	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
<b>Japan</b>	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
<b>China</b>	TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
<b>India</b>	TEL: 91-22-652-6696	FAX: 91-22-652-8914
<b>Middle East</b>	TEL: 9714-8834234	FAX: 9714-8834394
<b>Turkey</b>	TEL: 90-212-335-2553	FAX: 90-212-335-2500
<b>Chile</b>	TEL: 56-2-232-3185	FAX: 56-2-232-0923
<b>Brasil</b>	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
<b>South Africa</b>	TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
<b>Russia</b>	TEL: 7-095-737-3389	FAX: 7-095-737-3390
<b>Taiwan</b>	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
<b>D-Link Corp.</b>	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE  
Rev. 01 (Mar. 2003)  
Printed in Taiwan