



DU-128TA+

ISDN terminal adapter with USB 1.1 interface for connection to host.

## ISDN Terminal Adapter for PC

The DU-128TA+ is a USB-connected ISDN terminal adapter. It is ideally suited to give your PC access to the world of the Integrated Services Digital Network. Easy to install, easy to configure, this ISDN TA is fully compatible with ISDN networks.

### Fully Plug-and-Play

The DU-128TA+ is connected to your PC through a common USB 1.1 interface. You simply plug the USB port to your PC. Windows 98, 2000, ME & XP will automatically install and configure this terminal adapter for you.

### Versatile Functions

With this terminal adapter, you can have an ISDN telephone, answering machine, do file transfer, videotex, G3/G4 Fax functions, and get Internet access. This will bring you more versatility and efficiency in ISDN.

### Bundled ISDN Communication Software

An RVS-COM Lite v.2.0 software CD is provided with this adapter. This software provides the following functions:

- ISDN video conference (H.320)
- Analog and digital fax (G3/G4)
- Telephony
- Answerphone including remote playback
- File transfer/Eurofile transfer
- Softmodem
- Integration with Windows 2000, ME

---

### Key Features

- Supports USB 1.1 connection to PC
- Easy plug-and-play installation
- Full 128Kbps-bandwidth optimization over single ISDN line to corporate Intranet and Internet for web surfing, video conferencing and file transferring
- Compatible with major service providers which adopts major ISDN protocols (PPP, V.120, V.110, X.75, MLPPP)
- Supports data/fax/voice functions via communication software
- Bus-powered, no external power adapter required
- O.S. support: Windows 98, 2000, ME, XP

# DU-128TA+

## Technical Specifications

### Hardware

#### ISDN Interface

- Basic Rate Access (2B + D)
- S/T interface conforming to ITU-T I.430
- Protocols supported: ITU Q.921, Q.931 and ETSI NET 3

#### ISDN Line Rates

- 64Kbps on one B-channel (ISDN datamode)
- 128Kbps on two B-channels (multilink PPP)
- 16Kbps on D-channel (for signaling)

#### Host Interface

USB 1.1

#### LED Indicators

- USB (connection status)
- ISDN (Layer 1 ready/established, B-channel(s) status)

### Software

#### B Channel Protocols

- HDLC, X.75, T.70, V.110, V.120
- ISO 8208, PPP, Multi-link PPP
- G3 fax over B-channel
- 2400 analog modem
- Async-to-sync PPP conversion

#### D Channel Signaling Protocols

DSSI, VN3, BTNR191, NTT

#### Application Program Interfaces

- Virtual Com/modem Interface
- CAPI 2.0
- NDIS WAN mini-port

#### Operating System Support

- Microsoft Windows 98, 2000, ME, XP

### Physical & Environmental

#### Power Consumption

0.65 watts (max.)

#### Dimensions

79mm (L) x 58mm (W) x 22mm (H)

#### Weight

60 grams

#### Operating Temperature

0° - 50°C (32° - 122°F)

#### Storage Temperature

-25° - 55°C (-13° - 131°F)

#### Humidity

5% to 95%, non-condensing

#### Emission Certification

CE Class B

## ISDN Terminal Adapter

### Ordering Information

#### ISDN Terminal Adapter

DU-128TA+ 1 RJ-45 ISDN BRI port (S/T Interface)  
1 USB port

\* S/T interface requires an external NT-1 device

# D-Link®

Specifications subject to change without prior notice.  
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

<b>U.S.A.</b>	TEL: 1-949-788-0805	FAX: 1-949-753-7033
<b>Canada</b>	TEL: 1-905-829-5033	FAX: 1-905-829-5095
<b>Europe</b>	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511
<b>U.K.</b>	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511
<b>Germany</b>	TEL: 49-61- 96779900	FAX: 49-61-967799300
<b>France</b>	TEL: 33-1-30.23.86.88	FAX: 33-1-30.23.86.89
<b>Italy</b>	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723
<b>Iberia</b>	TEL: 34-93-4965751	FAX: 34-93-4965701
<b>Sweden</b>	TEL: 46-(0)8-564-61900	FAX: 46-(0)8-564-61901
<b>Norway</b>	TEL: 47-22-991890	FAX: 47-22-207039
<b>Denmark</b>	TEL: 45-43-96.90.40	FAX: 45-43-42.43.47
<b>Finland</b>	TEL: 358-9-622-91660	FAX: 358-9-622-91661
<b>Singapore</b>	TEL: 65-6774-6233	FAX: 65-6774-6322
<b>Australia</b>	TEL: 61-2-9417-7100	FAX: 61-2-9417-1077
<b>Japan</b>	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
<b>China</b>	TEL: 86-10-88097777	FAX: 86-10-88096789
<b>India</b>	TEL: 91-22-652-6696	FAX: 91-22-652-8914
<b>Middle East</b>	TEL: 202-2456176	FAX: 202-2456192
<b>South America</b>	TEL: 56-2-232-3185	FAX: 56-2-232-0923
<b>Brasil</b>	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
<b>South Africa</b>	TEL: 27(0)126652165	FAX: 27(0)126652186
<b>Russia</b>	TEL: 7-095-737-3389	FAX: 7-095-737-3390
<b>Taiwan</b>	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
<b>D-Link Corp.</b>	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE  
Rev. 01 (July 2002)  
Printed in Taiwan