





# **802.11b Wireless LAN CardBus Adapter**

The D-Link Air DWL-610 is a powerful CardBus adapter for notebook PCs. This adapter connects you to a 2.4GHz wireless LAN, giving you wireless access to the network. With fast 32-bit PC Card Type II interface, the DWL-610 provides industry standard interoperability, strong data security and ease of use ideal for notebook PC users requiring wireless network connection.

### Industry-standard Interoperability

With IEEE 802.11b wireless LAN industry standard compliance, the DWL-610 adapter provides network interoperability for wireless connectivity.

#### **Network Security**

Security is an issue when data is transmitted without the wires. In the air, transmitted data can be easily intercepted if not well protected by a security scheme. The DWL-610 provides the necessary security, using 64/128-bit industry-

standard WEP (Wired Equivalent Privacy) encryption protocol. Data privacy mechanism is based on a shared key algorithm, as described in the wireless LAN standard.

#### Easy Installation

With hot swap and plug-and-play capabilities, the DWL-610 adapter can be easily installed into a notebook PC to provide connectivity directly to another wireless enabled device (adhoc mode) or through an Access Point (infra-structure mode).

#### **Key Features**

- 32-bit high-performance CardBus (PC Card Type II) adapter for notebook PC
- IEEE 802.11b industry standard compliance
- 2.4GHz frequency band Direct Sequence Spread Spectrum (DSSS)
- 11Mbps data transfer rate
- Security with 64/128-bit WEP data encryption
- Supports Windows 98, 2000, ME, XP

## **Technical Specifications**

### Standards & Hardware Specifications

#### **LAN Standard**

IEEE 802.11b wireless LAN

#### **Adapter Type**

PC Card Type II CardBus

#### **Media Access Control Protocol**

CSMA/CA

#### **Network Architecture Types**

- Supports Ad-Hoc and Infrastructure Modes
- Cell to cell roaming

#### **Data Rates**

- 11 Mbps
- 5.5 Mbps
- 2 Mbps - 1 Mbps
- Auto fall-back

### **Data Rate & Modulation Scheme**

- 11Mbps: CCK
- 5.5Mbps: CCK
- 2Mbps: DQPSK
- 1Mbps: DBPSK

#### **Operating Channels**

- North America (FCC): 11
- Canada (DOC): 11
- Europe (ETSI): 13
- Japan (MKK): 14

### Sensitivity @ PER<0.08

- 11Mbps: -83dBm @ 8% PEP (Packet Error Rate)
- 2Mbps: -90dBm @ 8% PEP (Packet Error Rate)

#### Frequency Range

2.4 to 2.497 GHz ISM band

#### **Modulation Techniques**

- Direct Sequence Spread Spectrum (DSSS)
- Complementary Code Keying (CCK)
- 11-chip Barker Sequence

#### **Key Management**

Automatic Dynamic Key Allocation (ADKA) through public key

#### **Data Security**

64, 128-bit WEP (Wired Equivalent Privacy) encryption

Integrated Microstrip antenna

#### **Transmitter Output Power**

16dBm (typical)

Seamless roaming across cell boundaries within access point range

#### Range Coverage (Open Environment)

- Indoors: Up to 100 meters (328 feet)
- Outdoors: Up to 400 meters (1,312 feet) \*
- \* Environmental factors may adversely affect operating range

#### Physical & Environmental **Diagnostic LEDs**

- Link
- Activity

#### **Operating Voltage**

3.3VDC +/- 5%

#### **Power Consumption**

- Transmit mode: 350 mA (max.)
- Receive mode: 180 mA (max.)
- Sleep mode: 30 mA (max.)

## 2.4GHz Wireless LAN

#### **Dimensions**

115 (L) x 49 (W) x 5 (H) mm (adapter only)

40 grams (adapter only)

#### **Operating Temperature**

0° to 55 °C (32° to 131° F)

#### **Storage Temperature**

-20° to 75° C (-4° to 167° F)

#### Operating Humidity

10% to 90%, non-condensing

#### Storage Humidity

5% to 95%, non-condensing

#### **Emission Certification**

- FCC Class B
- CE Class B

#### MBTF (Mean Time Between Failure)

> 30,000 hours

#### Software

#### O.S. Support

Windows 98, 2000, ME, XP





## Ordering Information

**DWL-610** 802.11b Wireless LAN CardBus Adapter

Please specify your order as follows:

DWL-610/NA North America frequency

For Canada

DWL-610/EU EU frequency DWL-610/CN For China **TDWL-610** For Taiwan



prior notice.

D-Link is a registered trademark and D-LinkAir is a trademark of D-Link
Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

**CDWL-610** 

Canada Europe Germany France Benelux Italy Iberia Sweden Norway Denmark Finland Australia Japan China India Egypt UAE Turkey Israel Chile Brasil South Africa Russia

D-Link Corp.

TEL: 1-949-788-0805 TEL: 1-905-8295033 TEL: 44-20-8731-5555 TEL: 49-6196-77990 TEL: 33-1-30238688 TEL: 31-10-2045740 TEL: 39-2-2900-0676 TEL: 34-93-4090770 TEL: 46-(0)8564-61900 TEL: 47-22-309075 TEL: 45-43-969040 TEL: 358-9-2707-5080 TEL: 65-6774-6233 TEL: 61-2-8899-1800 TEL: 81-3-5434-9678 TEL: 86-10-8518-2533 TEL: 91-22-652-6696 TEL: 202-62-44615 TEL: 971-4-3916480 TEL: 90-212-335-2525 TEL: 972-9-9715700 TEL: 56-2-232-3185 TEL: 55-11-3094-2910 TEL: 27(0)1266-52165 TEL: 7-095-737-3389 TEL: 886-2-2910-2626

FAX: 1-949-753-7033 FAX: 1-905-8295095 FAX: 44-20-8731-5511 FAX: 49-6196-7799300 FAX: 33-1-30238689 FAX: 31-10-2045880 FAX: 39-2-2900-1723 FAX: 34-93-4910795 FAX: 46-(0)8564-61901 FAX: 47-22-309085 FAX: 45-43-424347 FAX: 358-9-2707-5081 FAX: 65-6774-6322 FAX: 61-2-8899-1868 FAX: 81-3-5434-9868 FAX: 86-10-8518-2250 FAX: 91-22-652-8914 FAX: 202-62-44583 FAX: 971-4-3908881 FAX: 90-212-335-2500 FAX: 972-9-971-5601 FAX: 55-11-3094-2921 FAX: 27(0)1266-52186 FAX: 7-095-737-3390 FAX: 886-2-2910-1515 TEL: 886-2-2916-1600 FAX: 886-2-2914-6299



RECYCLABLE Rev. 01 (Jun. 2003)