



— DWL-700AP

## 802.11b Wireless LAN Access Point

The D-Link Air DWL-700AP Access Point is designed to give 2.4GHz wireless LAN users low-cost yet secure access to an IEEE 802.11b wireless Local Area Network (LAN). This Access Point combines industry standards with versatile functions like repeater mode, and enhanced IEEE 802.11i security features like WEP, TKIP, and AES to give you wireless LAN interoperability and functionality at an affordable price.

### Wireless Access

The DWL-700AP Access Point connects the wireless LAN nodes (workstations, print servers, etc.) together via a 2.4GHz IEEE 802.11b wireless interface. It listens to all data traffic and maintains a dynamically updated MAC address database. When necessary, IP addresses are matched to MAC addresses and information is stored in the database as well. A 10/100Mbps Fast Ethernet port provides a bridge between a wireless network and wired network. The DWL-700AP converts data packets over a wired Ethernet LAN into radio signals to be used on the wireless network and vice versa.

### Built-in Repeater Function

The DWL-700AP can be configured to operate in any one of the following modes: (1) as a wireless access point, (2) a wireless client or (3) a repeater. With these built-in functions, the DWL-700AP gives you the flexibility to

configure the device to as an access point at home or the office with normal wireless operation range requirements, or as a repeater that connects 2 wireless networks together when the number of wireless users increases and spreads in a wider area.

### Network Security

In the air, transmitted data can be easily intercepted if not well protected by a security scheme. The DWL-700AP provides the necessary security, using the enhanced 64/128-bit industry-standard WEP (Wired Equivalent Privacy) encryption protocol. It also provides IEEE 802.11i security features such as embedded AES/TKIP security engine (hardware supported).

### Web-based & SNMP Configuration/Management

The DWL-700AP can be configured and managed by HTTP (web-based configuration) or SNMP (SNMP v.2 support) through built-in MIBs. DHCP client and server are supported.

### Key Features

- 802.11b 2.4GHz industry standard with wide range of wireless LAN interoperability
- 11Mbps data transfer rates
- 10/100Mbps auto-sensing Fast Ethernet port to bridge wireless LAN to Ethernet-based network
- Built-in repeater function
- Embedded AES/TKIP security engine
- SNMP v2 support
- Client access control via MAC address
- Configuration by HTTP and SNMP
- Management features: SNMP, HTTP, DHCP Server & Client

# DWL-700AP

## Technical Specifications

### Standards

- IEEE 802.11b wireless LAN
- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet

### Wireless LAN to Ethernet Interface

Through RJ-45 10/100Mbps Fast Ethernet port

### Frequency Range

2.4GHz to 2.4835GHz

### Modulation Techniques

Direct Sequence Spread Spectrum (DSSS)

### Data Rates

- 11 Mbps
- 5.5 Mbps
- 2 Mbps
- 1 Mbps
- Auto fall-back

### Data Rate & Modulation Scheme

- 11Mbps: CCK
- 5.5Mbps: CCK
- 2Mbps: Barker
- 1Mbps: Barker

### Operating Channels

- North America (FCC): 11
- Canada (DOC): 11
- Europe (ETSI): 13

### Antenna

Detachable 2dBi Gain antenna with reverse SMA connector

### Receive Sensitivity

@<8% -82 dBm (typical)

### Transmit Output Power

18dBm (typical)

### Operating Range

- Indoors: up to 100 m (328 feet) \*
- Outdoors: up to 300 m (984 feet) \*

\* Environmental factors may adversely affect operating range

### Operating Modes

- Access Point
- Wireless client
- Repeater

### Security

Data encryption: 64-bit, 128-bit-bit WEP (Wired Equivalent Privacy)

### Device Management

- Web-based through Internet Explorer v6 or later; Netscape Navigator v6 or later; or other Java-enabled browsers
- DHCP Server and Client

## Physical & Environmental

### Power Input

- DC 5V, 2.0A
- Uses external AC power adapter

### Dimensions

142 (L) x 109 (W) x 31 (H) mm  
(5.6 x 4.3 x 1.2 inches)

### Weight

200 grams (0.44 lb.)

### Operating Temperature

0° to 55° C (32° to 149° F)

### Storing Temperature

-20° to 75° C (4° to 167° F)

### Humidity

Up to 95%, non-condensing

## 2.4GHz Wireless LAN

### Emission

- FCC Class B
- CE Class B

### Box Includes

- DWL-700AP Wireless Access Point
- User's Manual on CD
- Quick Installation Guide
- 1.8 m Cat. 5 Ethernet straight-through cable
- Power Adapter



## Ordering Information

**DWL-700AP** 802.11b Wireless LAN Access Point

*Please specify your order as follows:*

<b>BDWL-700AP</b>	US standard power adapter, North America frequency (USA packaging)
<b>TDWL-700AP</b>	US standard power adapter, North America frequency (Taiwan packaging)
<b>DWL-700AP/ANA</b>	US standard power adapter, North America frequency
<b>DWL-700AP/ENA</b>	EU standard power adapter, North America frequency
<b>DWL-700AP/BEU</b>	UK standard power adapter, EU frequency
<b>DWL-700AP/EEU</b>	EU standard power adapter, EU frequency
<b>DWL-700AP/NEU</b>	Australia standard power adapter, EU frequency
<b>DWL-700AP/CN</b>	For use in China (China packaging)

# D-Link®

Specifications subject to change without prior notice.  
D-Link is a registered trademark and D-LinkAir is a trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

<b>U.S.A</b>	TEL: 1-949-788-0805	FAX: 1-949-753-7033
<b>Canada</b>	TEL: 1-905-8295033	FAX: 1-905-8295095
<b>Europe</b>	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
<b>Germany</b>	TEL: 49-6196-77990	FAX: 49-6196-7799300
<b>France</b>	TEL: 33-1-30238688	FAX: 33-1-30238689
<b>Benelux</b>	TEL: 31-10-2045740	FAX: 31-10-2045880
<b>Italy</b>	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
<b>Iberia</b>	TEL: 34-93-4090770	FAX: 34-93-4910795
<b>Sweden</b>	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
<b>Norway</b>	TEL: 47-22-309075	FAX: 47-22-309085
<b>Denmark</b>	TEL: 45-43-969040	FAX: 45-43-424347
<b>Finland</b>	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
<b>Singapore</b>	TEL: 65-6774-6233	FAX: 65-6774-6322
<b>Australia</b>	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
<b>Japan</b>	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
<b>China</b>	TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
<b>India</b>	TEL: 91-22-652-6696	FAX: 91-22-652-8914
<b>Egypt</b>	TEL: 202-62-44615	FAX: 202-62-44583
<b>UAE</b>	TEL: 971-4-3916480	FAX: 971-4-3908881
<b>Turkey</b>	TEL: 90-212-335-2525	FAX: 90-212-335-2500
<b>Israel</b>	TEL: 972-9-9715700	FAX: 972-9-971-5601
<b>Chile</b>	TEL: 56-2-232-3185	FAX: 56-2-232-0923
<b>Brasil</b>	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
<b>South Africa</b>	TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
<b>Russia</b>	TEL: 7-095-737-3389	FAX: 7-095-737-3390
<b>Taiwan</b>	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
<b>D-Link Corp.</b>	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE  
Rev. 01 (Jul. 2003)